

THE O «SUSTAINABLE DEVELOPMENT»

→ Environmentally friendly R290 fluid

THE **O** «USER»

- → Easy to move with its wheels and handles
- → Easy to read with its digital display
- → Remotely controllable with RC unit

THE O «TECHNOLOGY»

- → Sealing kit included
- → Evacuation of condensates by evaporation

→ PRODUCTS

- RC08C remote control included
- Compact & design

FEATURES

AIR QUALITY/CLEAN:





USER FUNCTIONS:











INSTALLER FUNCTIONS:



| Indoor unit | | AW-MFH009-C41 | AW-MFH012-C41 |
|--|-------|------------------|---------------|
| Phase | | Single phase | Single phase |
| COOLING | | | |
| Rated power | kW | 2.93 | 3.52 |
| Rated power input | kW | 0.945 | 1.357 |
| Current | А | 4.5 | 5.9 |
| EER/Energy label | | 3.10/A+ | 2.60/A |
| Operating limits | °C | 17°/35° Dry bulb | |
| INDOOR UNIT | | | |
| Туре | | Monobloc | Monobloc |
| Sound pressure level to 1 m (LS/MS/HS) | dB(A) | 50/51/52 | 50/51/52 |
| Sound power Level | dB(A) | 56 | 63 |
| Airflow (LS/MS/HS) | m³/h | 355/370/420 | 355/370/420 |
| Diameter flexible emission duct | mm | 150 | |
| Length range of heat emission duct | m | 0.50 - 1.5 | |
| Dehumidification | l/h | 1.6 | 1.8 |
| Outline dimensions (WxHxD) | mm | 467x765x397 | 467x765x397 |
| Package dimensions (WxHxD) | mm | 515x890x440 | 515x890x440 |
| Net weight/Gross weight | kg | 31.8/35.7 | 33/36.5 |
| Part number | | 7MB021060 | 7MB021061 |
| POWER SUPPLY | | | |
| Phase/Voltage/Frequency | | 1P/230V/50Hz | 1P/230V/50Hz |
| PIPE LINE | | | |
| Refrigerant/GWP | | R290/20 | R290/20 |
| Charge | kg | 0.21 | 0.22 |
| Packing 8 pieces minimum | | | |

^{*} Packing 8 pieces minimum

MFH TECHNICAL DATA

