

Appliance - Split type air conditioner

| | | |
|--------------|-----------------|-----------------|
| Outdoor unit | Single Inverter | RAV-GM1101ATP-E |
| Indoor unit | Ceiling | RAV-RM1101CTP-E |

| Function | | Design load | | | Seasonal efficiency | | | |
|-------------------|---|-----------------------------|----------|--------|---------------------|---------|------|----|
| Cooling | Y | Cooling | Pdesignc | 9.5 kW | Cooling | SEER | 5.86 | A+ |
| Heating - Average | Y | Heating/Average | Pdesignh | 7.6 kW | Heating/Average | SCOP(A) | 4.27 | A+ |
| Heating - Warmer | N | Capacity control = Variable | | | | | | |
| Heating - Colder | N | | | | | | | |

Cooling

| Capacity | | | Efficiency | | |
|--|-----|---------|---|------|-------|
| Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj. | | | Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj. | | |
| Tj=35°C | Pdc | 9.50 kW | Tj=35°C | EERd | 3.22 |
| Tj=30°C | Pdc | 7.00 kW | Tj=30°C | EERd | 4.94 |
| Tj=25°C | Pdc | 4.50 kW | Tj=25°C | EERd | 7.05 |
| Tj=20°C | Pdc | 4.00 kW | Tj=20°C | EERd | 11.23 |

Heating (Average climate)

| Capacity | | | Efficiency | | |
|--|-----|---------|--|------|------|
| Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj. | | | Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj. | | |
| Tj=-7°C | Pdh | 6.72 kW | Tj=-7°C | COPd | 2.66 |
| Tj=2°C | Pdh | 4.09 kW | Tj=2°C | COPd | 4.33 |
| Tj=7°C | Pdh | 2.85 kW | Tj=7°C | COPd | 5.64 |
| Tj=12°C | Pdh | 3.03 kW | Tj=12°C | COPd | 6.80 |
| Tj=bivalent temperature | Pdh | 6.72 kW | Tj=bivalent temperature | COPd | 2.66 |
| Tj=operation limit | Pdh | 4.57 kW | Tj=operation limit | COPd | 1.60 |
| Bivalent temperature | | -7 °C | | | |
| Operation limit temperature | | -15 °C | | | |

Electricity

Electric power input in power modes other than "on mode"

Seasonal electricity consumption

| | | | | | | | |
|-----------------------|------|-------|----|-----------------|-------|------|-------|
| off mode | Poff | 0.014 | kW | Cooling | QCE | 567 | kWh/a |
| standby mode | Psb | 0.014 | kW | Heating/Average | QHE/A | 2490 | kWh/a |
| thermostat-off mode | Pto | 0.078 | kW | Heating/Warmer | QHE/B | x | kWh/a |
| crankcase heater mode | Pck | 0.000 | kW | Heating/Colder | QHE/C | x | kWh/a |

Refrigerant

| | | | | | | | |
|--------------------------|-----|-----|--|------|-----------------------|--|--|
| Type | | R32 | | | | | |
| Weight | | | | 2.10 | kg | | |
| Global Warming Potential | GWP | | | 675 | kgCO ₂ eq. | | |

Sound power level - db(A)

Rated air flow - m³/h

| | Cooling | Heating | | Cooling | Heating |
|-----------------|---------|---------|-----------------|---------|---------|
| RAV-GM1101ATP-E | 70 | 74 | RAV-GM1101ATP-E | 4080 | 4080 |
| RAV-RM1101CTP-E | 59 | 59 | RAV-RM1101CTP-E | 1860 | 1860 |

Dimensions

| | Height | Width | Depth | Weight |
|-----------------|--------|---------|--------|--------|
| RAV-GM1101ATP-E | 890 mm | 900 mm | 320 mm | 68 kg |
| RAV-RM1101CTP-E | 235 mm | 1586 mm | 690 mm | 37 kg |

| | |
|---------------------|------------------------|
| Harmonised standard | EN14511:2007 , EN12102 |
|---------------------|------------------------|

| | |
|---|----------------------------------|
| Calculation methods - Measurement standards | PrEN 14825: 2011 chapter 8 and 9 |
|---|----------------------------------|

| | |
|--|---|
| Contact details for obtaining more information | Importer/Distributor in EU: Toshiba Carrier UK Ltd. Porsham Close, Belliver Industrial Estate, PLYMOUTH, Devon, PL6 7DB. United Kingdom |
|--|---|

| | |
|----------|-----------------------------|
| Supplier | TOSHIBA CARRIER CORPORATION |
|----------|-----------------------------|

| | |
|-------------|-----------------|
| Indoor unit | RAV-RM1101CTP-E |
|-------------|-----------------|

| | |
|--------------|-----------------|
| Outdoor unit | RAV-GM1101ATP-E |
|--------------|-----------------|

Sound power level

| | | |
|-----------------------|----|----|
| indoor unit (cooling) | dB | 59 |
|-----------------------|----|----|

| | | |
|------------------------|----|----|
| outdoor unit (cooling) | dB | 70 |
|------------------------|----|----|

| | | |
|-----------------------|----|----|
| indoor unit (heating) | dB | 59 |
|-----------------------|----|----|

| | | |
|------------------------|----|----|
| outdoor unit (heating) | dB | 74 |
|------------------------|----|----|

Refrigerant

| | | |
|------|--|-----|
| Type | | R32 |
|------|--|-----|

| | | |
|--------------------------|----------------------|-----|
| Global Warming Potential | kgCO ₂ eq | 675 |
|--------------------------|----------------------|-----|

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 1975. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 1975 times higher than 1 kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

Cooling

| | | |
|-------------------------|--|----|
| Energy efficiency class | | A+ |
|-------------------------|--|----|

| | | |
|-------------------------------------|----|-----|
| Design load (P _{designc}) | kW | 9.5 |
|-------------------------------------|----|-----|

| | | |
|----------------------------|--|------|
| Seasonal efficiency (SEER) | | 5.86 |
|----------------------------|--|------|

| | | |
|---|-----------|-----|
| Seasonal electricity consumption (Q _{CE}) | kWh/annum | 567 |
|---|-----------|-----|

Heating

| | | Heating/Average | Heating/Warmer | Heating/Colder |
|---|-----------|-----------------|----------------|----------------|
| Energy efficiency class | | A+ | x | x |
| Design load (Pdesignh) | kW | 7.6 | x,x | x,x |
| Seasonal efficiency (SCOP) | | 4.27 | x,xx | x,xx |
| Seasonal electricity consumption (Q _{H,E}) | kWh/annum | 2490 | x | x |
| Back up heating capacity | kW | 1.69 | | |
| Declared capacity for heating, at indoor temperature 20°C and outdoor temperature T_j. | | | | |
| T _j = -7°C (Pdh) | kW | 6.72 | - | x,xx |
| T _j = 2°C (Pdh) | kW | 4.09 | x,xx | x,xx |
| T _j = 7°C (Pdh) | kW | 2.85 | x,xx | x,xx |
| T _j = 12°C (Pdh) | kW | 3.03 | x,xx | x,xx |
| T _j =bivalent temperature (Pdh) | kW | 6.72 | x,xx | x,xx |
| T _j =operation limit (Pdh) | kW | 4.57 | x,xx | x,xx |
| T _j = -15°C (Pdh) | kW | - | - | x,xx |