

Appliance - Split type air conditioner

Outdoor unit	Single Inverter	RAV-GP561ATP-E
Indoor unit	Ceiling	RAV-RM561CTP-E

Function		Design load			Seasonal efficiency			
Cooling	Y	Cooling	Pdesignc	5.0 kW	Cooling	SEER	6.76	A++
Heating - Average	Y	Heating/Average	Pdesignh	3.8 kW	Heating/Average	SCOP(A)	4.70	A++
Heating - Warmer	N	Capacity control = Variable						
Heating - Colder	N							

Cooling

Capacity				Efficiency		
Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.				Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.		
Tj=35°C	Pdc	5.00 kW		Tj=35°C	EERd	3.65
Tj=30°C	Pdc	3.68 kW		Tj=30°C	EERd	5.43
Tj=25°C	Pdc	2.37 kW		Tj=25°C	EERd	8.41
Tj=20°C	Pdc	1.05 kW		Tj=20°C	EERd	11.78

Heating (Average climate)

Capacity				Efficiency		
Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.				Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.		
Tj=-7°C	Pdh	3.36 kW		Tj=-7°C	COPd	3.13
Tj=2°C	Pdh	2.05 kW		Tj=2°C	COPd	4.63
Tj=7°C	Pdh	1.32 kW		Tj=7°C	COPd	6.03
Tj=12°C	Pdh	0.58 kW		Tj=12°C	COPd	7.25
Tj=bivalent temperature	Pdh	3.36 kW		Tj=bivalent temperature	COPd	3.13
Tj=operation limit	Pdh	0.67 kW		Tj=operation limit	COPd	0.92
Bivalent temperature		-7 °C				
Operation limit temperature		-27 °C				

Electricity

Electric power input in power modes other than "on mode"

Seasonal electricity consumption

off mode	Poff	0.007	kW	Cooling	QCE	259	kWh/a
standby mode	Psb	0.007	kW	Heating/Average	QHE/A	1130	kWh/a
thermostat-off mode	Pto	0.034	kW	Heating/Warmer	QHE/B	x	kWh/a
crankcase heater mode	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

Refrigerant

Type		R32					
Weight					1.35	kg	
Global Warming Potential	GWP				675	kgCO ₂ eq.	

Sound power level - db(A)

Rated air flow - m³/h

	Cooling	Heating		Cooling	Heating
RAV-GP561ATP-E	63	65	RAV-GP561ATP-E	2250	2070
RAV-RM561CTP-E	52	52	RAV-RM561CTP-E	900	900

Dimensions

	Height	Width	Depth	Weight
RAV-GP561ATP-E	630 mm	799 mm	299 mm	45 kg
RAV-RM561CTP-E	235 mm	952 mm	690 mm	23 kg

Harmonised standard	EN14511:2007, EN12102
---------------------	-----------------------

Calculation methods - Measurement standards	PrEN 14825: 2011 chapter 8 and 9
---	----------------------------------

Contact details for obtaining more information	Importer/Distributor in EU: Toshiba Carrier UK Ltd. Porsham Close, Belliver Industrial Estate, PLYMOUTH, Devon, PL6 7DB. United Kingdom
--	---

Supplier	TOSHIBA CARRIER CORPORATION
----------	-----------------------------

Indoor unit	RAV-RM561CTP-E
-------------	----------------

Outdoor unit	RAV-GP561ATP-E
--------------	----------------

Sound power level

indoor unit (cooling)	dB	52
-----------------------	----	----

outdoor unit (cooling)	dB	63
------------------------	----	----

indoor unit (heating)	dB	52
-----------------------	----	----

outdoor unit (heating)	dB	65
------------------------	----	----

Refrigerant

Type		R32
------	--	-----

Global Warming Potential	kgCO ₂ eq	675
--------------------------	----------------------	-----

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 1975. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 1975 times higher than 1 kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

Cooling

Energy efficiency class		A++
-------------------------	--	-----

Design load (P _{designc})	kW	5.0
-------------------------------------	----	-----

Seasonal efficiency (SEER)		6.76
----------------------------	--	------

Seasonal electricity consumption (Q _{CE})	kWh/annum	259
---	-----------	-----

Heating

		Heating/Average	Heating/Warmer	Heating/Colder
Energy efficiency class		A++	x	x
Design load (Pdesignh)	kW	3.8	x,x	x,x
Seasonal efficiency (SCOP)		4.70	x,xx	x,xx
Seasonal electricity consumption (Q _{HE})	kWh/annum	1130	x	x
Back up heating capacity	kW	0.84		
Declared capacity for heating, at indoor temperature 20°C and outdoor temperature Tj.				
Tj= -7°C (Pdh)	kW	3.36	-	x,xx
Tj= 2°C (Pdh)	kW	2.05	x,xx	x,xx
Tj= 7°C (Pdh)	kW	1.32	x,xx	x,xx
Tj= 12°C (Pdh)	kW	0.58	x,xx	x,xx
Tj=bivalent temperature (Pdh)	kW	3.36	x,xx	x,xx
Tj=operation limit (Pdh)	kW	0.67	x,xx	x,xx
Tj= -15°C (Pdh)	kW	-	-	x,xx