Appliance - Split type air conditioner

Outdoor unit	Single Inverter	RAV-GP1101AT-E
Indoor unit	Ceiling	RAV-RM1101CTP-E

Function

Cooling	Y
Heating - Average	Y
Heating - Warmer	N
Heating - Colder	N

Design load

Cooling	Pdesignc	10.0	kW
Heating/Average	Pdesignh	9.2	kW

Capacity control = Variable

Seasonal efficiency

Cooling	SEER	8.23	A++
Heating/Average	SCOP(A)	4.72	A++

Cooling

Capacity

Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.

Efficiency

Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.

Tj=35℃	Pdc	10.00	kW	Tj=35℃	EERd	4.48
Tj=30℃	Pdc	7.27	kW	Tj=30℃	EERd	6.11
Tj=25℃	Pdc	4.72	kW	Tj=25℃	EERd	10.73
Tj=20℃	Pdc	3.63	kW	Tj=20℃	EERd	15.78

Heating (Average climate)

Capacity

Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.

Efficiency

Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.

Tj=-7°C	Pdh	8.14	kW	Tj=-7°C	COPd	3.12
Tj=2°C	Pdh	4.96	kW	Tj=2°C	COPd	4.72
Tj=7°C	Pdh	3.21	kW	Tj=7°C	COPd	6.06
Tj=12°C	Pdh	3.07	kW	Tj=12°C	COPd	7.68
Tj=bivalent temperature	Pdh	8.14	kW	Tj=bivalent temperature	COPd	3.12
Tj=operation limit	Pdh	1.63	kW	Tj=operation limit	COPd	0.92
Bivalent temperature		-7	°C			
Operation limit temperature		-27	°C			

Electricity

Electric power input in power modes other than "on mode"				Seasonal electricity consumption			
off mode	Poff	0.007	kW	Cooling	QCE	425	kWh/a
standby mode	Psb	0.007	kW	Heating/Average	QHE/A	2726	kWh/a
thermostat-off mode	Pto	0.086	kW	Heating/Warmer	QHE/B	x	kWh/a
crankcase heater mode	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

Refrigerant

Type		R32	
Weight		3.10	kg
Global Warming Potential	GWP	675	$kgCO_2eq.$

Sound power level - db(A)

	Cooling	Heating
RAV-GP1101AT-E	66	67
RAV-RM1101CTP-E	59	59

Rated air flow - m^3/h

	Cooling	Heating
RAV-GP1101AT-E	6960	6960
RAV-RM1101CTP-E	1860	1860

Dimensions

	Height	Width	Depth	Weight
RAV-GP1101AT-E	1550 mm	1010 mm	370 mm	104 kg
RAV-RM1101CTP-E	235 mm	1586 mm	690 mm	37 kg

Harmonised standard	EN14511:2007 , EN12102
Calculation methods - Measurement standards	PrEN 14825： 2011 chapter 8 and 9
Contact details for obtaining more information	Importer/Distributor in EU: Toshiba Carrier UK Ltd. Porsham Close, Belliver Industrial Estate, PLYMOUTH, Devon, PL6 7DB. United Kingdom

Supplier	TOSHIBA CARRIER CORPORATION

Indoor unit	RAV-RM1101CTP-E
Outdoor unit	RAV-GP1101AT-E

Sound power level

indoor unit (cooling)	dB	59
outdoor unit (cooling)	dB	66
indoor unit (heating)	dB	59
outdoor unit (heating)	dB	67

Refrigerant

Type		R32
Global Warming Potential	$kgCO_2eq$	675

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 1975. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 1975 times higher than 1 kg of CO2, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

Cooling

Energy efficiency class		A++
Design load (Pdesignc)	kW	10.0
Seasonal efficiency (SEER)		8.23
Seasonal electricity consumption (Q_{CE})	kWh/annum	425

Heating

		Heating/Average	Heating/Warmer	Heating/Colder
Energy efficiency class		A++	x	x
Design load (Pdesignh)	kW	9.2	x,x	x,x
Seasonal efficiency (SCOP)		4.72	x,xx	x,xx
Seasonal electricity consumption (Q_{HE})	kWh/annum	2726	x	x
Back up heating capacity	kW	2.04		
Declared capacity for heating, at indoor temperature 20°C and outdoor temperature Tj.				
Tj= -7°C (Pdh)	kW	8.14	-	x,xx
Tj= 2°C (Pdh)	kW	4.96	x,xx	x,xx
Tj= 7°C (Pdh)	kW	3.21	x,xx	x,xx
Tj= 12°C (Pdh)	kW	3.07	x,xx	x,xx
Tj=bivalent temperature (Pdh)	kW	8.14	x,xx	x,xx
Tj=operation limit (Pdh)	kW	1.63	x,xx	x,xx
Tj= -15°C (Pdh)	kW	-	-	x,xx