

## Appliance - Split type air conditioner

|              |                 |                 |
|--------------|-----------------|-----------------|
| Outdoor unit | Single Inverter | RAV-GP1101AT-E  |
| Indoor unit  | 4-way Cassette  | RAV-RM1101UTP-E |

| Function          |   | Design load                 |          |      | Seasonal efficiency |                 |         |      |     |
|-------------------|---|-----------------------------|----------|------|---------------------|-----------------|---------|------|-----|
| Cooling           | Y | Cooling                     | Pdesignc | 10.0 | kW                  | Cooling         | SEER    | 8.65 | A++ |
| Heating - Average | Y | Heating/Average             | Pdesignh | 9.2  | kW                  | Heating/Average | SCOP(A) | 4.73 | A++ |
| Heating - Warmer  | N | Capacity control = Variable |          |      |                     |                 |         |      |     |
| Heating - Colder  | N |                             |          |      |                     |                 |         |      |     |

## Cooling

| Capacity   |     |       |    | Efficiency  |      |       |
|--|-----|-------|----|---|------|-------|
| Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj. |     |       |    | Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj. |      |       |
| Tj=35°C  | Pdc | 10.00 | kW | Tj=35°C   | EERd | 4.69  |
| Tj=30°C  | Pdc | 7.34  | kW | Tj=30°C   | EERd | 6.44  |
| Tj=25°C  | Pdc | 4.70  | kW | Tj=25°C   | EERd | 10.93 |
| Tj=20°C  | Pdc | 3.81  | kW | Tj=20°C   | EERd | 18.14 |

## Heating (Average climate)

| Capacity   |     |      |    | Efficiency   |      |      |
|--|-----|------|----|--|------|------|
| Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj. |     |      |    | Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj. |      |      |
| Tj=-7°C  | Pdh | 8.14 | kW | Tj=-7°C  | COPd | 3.01 |
| Tj=2°C   | Pdh | 4.90 | kW | Tj=2°C   | COPd | 4.71 |
| Tj=7°C   | Pdh | 3.19 | kW | Tj=7°C   | COPd | 6.25 |
| Tj=12°C  | Pdh | 3.05 | kW | Tj=12°C  | COPd | 8.03 |
| Tj=bivalent temperature  | Pdh | 8.14 | kW | Tj=bivalent temperature  | COPd | 3.01 |
| Tj=operation limit   | Pdh | 1.63 | kW | Tj=operation limit   | COPd | 0.89 |
| Bivalent temperature   |     | -7   | °C |  |      |      |
| Operation limit temperature  |     | -27  | °C |  |      |      |

## Electricity

Electric power input in power modes other than "on mode"

Seasonal electricity consumption

|                       |      |       |    |                 |       |      |       |
|-----------------------|------|-------|----|-----------------|-------|------|-------|
| off mode              | Poff | 0.007 | kW | Cooling         | QCE   | 405  | kWh/a |
| standby mode          | Psb  | 0.007 | kW | Heating/Average | QHE/A | 2719 | kWh/a |
| thermostat-off mode   | Pto  | 0.086 | kW | Heating/Warmer  | QHE/B | x    | kWh/a |
| crankcase heater mode | Pck  | 0.000 | kW | Heating/Colder  | QHE/C | x    | kWh/a |

## Refrigerant

|                          |     |     |  |  |  |      |                       |
|--------------------------|-----|-----|--|--|--|------|-----------------------|
| Type                     |     | R32 |  |  |  |      |                       |
| Weight                   |     |     |  |  |  | 3.10 | kg                    |
| Global Warming Potential | GWP |     |  |  |  | 675  | kgCO <sub>2</sub> eq. |

## Sound power level - db(A)

## Rated air flow - m<sup>3</sup>/h

|                 | Cooling | Heating |                 | Cooling | Heating |
|-----------------|---------|---------|-----------------|---------|---------|
| RAV-GP1101AT-E  | 66      | 67      | RAV-GP1101AT-E  | 6960    | 6960    |
| RAV-RM1101UTP-E | 58      | 58      | RAV-RM1101UTP-E | 2010    | 2010    |

## Dimensions

|                 | Height  | Width   | Depth  | Weight |
|-----------------|---------|---------|--------|--------|
| RAV-GP1101AT-E  | 1550 mm | 1010 mm | 370 mm | 104 kg |
| RAV-RM1101UTP-E | 319 mm  | 840 mm  | 840 mm | 24 kg  |

|                     |                       |
|---------------------|-----------------------|
| Harmonised standard | EN14511:2007, EN12102 |
|---------------------|-----------------------|

|   |                                  |
|---|----------------------------------|
| Calculation methods - Measurement standards | PrEN 14825: 2011 chapter 8 and 9 |
|---|----------------------------------|

|  |   |
|--|---|
| Contact details for obtaining more information | Importer/Distributor in EU:<br>Toshiba Carrier UK Ltd.<br>Porsham Close, Belliver Industrial Estate,<br>PLYMOUTH, Devon, PL6 7DB.<br>United Kingdom |
|--|---|

|          |                             |
|----------|-----------------------------|
| Supplier | TOSHIBA CARRIER CORPORATION |
|----------|-----------------------------|

|             |                 |
|-------------|-----------------|
| Indoor unit | RAV-RM1101UTP-E |
|-------------|-----------------|

|              |                |
|--------------|----------------|
| Outdoor unit | RAV-GP1101AT-E |
|--------------|----------------|

## Sound power level

|                       |    |    |
|-----------------------|----|----|
| indoor unit (cooling) | dB | 58 |
|-----------------------|----|----|

|                        |    |    |
|------------------------|----|----|
| outdoor unit (cooling) | dB | 66 |
|------------------------|----|----|

|                       |    |    |
|-----------------------|----|----|
| indoor unit (heating) | dB | 58 |
|-----------------------|----|----|

|                        |    |    |
|------------------------|----|----|
| outdoor unit (heating) | dB | 67 |
|------------------------|----|----|

## Refrigerant

|      |  |     |
|------|--|-----|
| Type |  | R32 |
|------|--|-----|

|                          |                      |     |
|--------------------------|----------------------|-----|
| Global Warming Potential | kgCO <sub>2</sub> eq | 675 |
|--------------------------|----------------------|-----|

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 1975. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 1975 times higher than 1 kg of CO<sub>2</sub>, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

## Cooling

|                         |  |     |
|-------------------------|--|-----|
| Energy efficiency class |  | A++ |
|-------------------------|--|-----|

|                                     |    |      |
|-------------------------------------|----|------|
| Design load (P <sub>designc</sub> ) | kW | 10.0 |
|-------------------------------------|----|------|

|                            |  |      |
|----------------------------|--|------|
| Seasonal efficiency (SEER) |  | 8.65 |
|----------------------------|--|------|

|   |           |     |
|---|-----------|-----|
| Seasonal electricity consumption (Q <sub>CE</sub> ) | kWh/annum | 405 |
|---|-----------|-----|

## Heating

|  |           | Heating/Average | Heating/Warmer | Heating/Colder |
|--|-----------|-----------------|----------------|----------------|
| Energy efficiency class  |           | A++             | x              | x              |
| Design load (Pdesignh)   | kW        | 9.2             | x,x            | x,x            |
| Seasonal efficiency (SCOP)   |           | 4.73            | x,xx           | x,xx           |
| Seasonal electricity consumption (Q <sub>HE</sub> )  | kWh/annum | 2719            | x              | x              |
| Back up heating capacity   | kW        | 2.04            |                |                |
| <b>Declared capacity for heating, at indoor temperature 20°C and outdoor temperature Tj.</b> |           |                 |                |                |
| Tj= -7°C (Pdh)   | kW        | 8.14            | -              | x,xx           |
| Tj= 2°C (Pdh)  | kW        | 4.90            | x,xx           | x,xx           |
| Tj= 7°C (Pdh)  | kW        | 3.19            | x,xx           | x,xx           |
| Tj= 12°C (Pdh)   | kW        | 3.05            | x,xx           | x,xx           |
| Tj=bivalent temperature (Pdh)  | kW        | 8.14            | x,xx           | x,xx           |
| Tj=operation limit (Pdh)   | kW        | 1.63            | x,xx           | x,xx           |
| Tj= -15°C (Pdh)  | kW        | -               | -              | x,xx           |