

Appliance - Split type air conditioner

Outdoor unit	Single Inverter	RAV-GP1101AT8-E
Indoor unit	4-way Cassette	RAV-RM561UTP-E
Indoor unit	4-way Cassette	RAV-RM561UTP-E

Function

Design load

Seasonal efficiency

Cooling	Y	Cooling	Pdesignc	10.0	kW	Cooling	SEER	7.06	A++
Heating - Average	Y	Heating/Average	Pdesignh	9.5	kW	Heating/Average	SCOP(A)	4.36	A+
Heating - Warmer	N	Capacity control = Variable							
Heating - Colder	N								

Cooling

Capacity				Efficiency			
Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.				Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.			
Tj=35°C	Pdc	10.00	kW	Tj=35°C	EERd		4.31
Tj=30°C	Pdc	7.37	kW	Tj=30°C	EERd		6.19
Tj=25°C	Pdc	4.74	kW	Tj=25°C	EERd		9.67
Tj=20°C	Pdc	4.14	kW	Tj=20°C	EERd		12.94

Heating (Average climate)

Capacity				Efficiency			
Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.				Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.			
Tj=-7°C	Pdh	8.40	kW	Tj=-7°C	COPd		2.75
Tj=2°C	Pdh	5.12	kW	Tj=2°C	COPd		4.16
Tj=7°C	Pdh	3.50	kW	Tj=7°C	COPd		6.36
Tj=12°C	Pdh	3.48	kW	Tj=12°C	COPd		7.25
Tj=bivalent temperature	Pdh	8.40	kW	Tj=bivalent temperature	COPd		2.75
Tj=operation limit	Pdh	4.03	kW	Tj=operation limit	COPd		1.64
Bivalent temperature		-7	°C				
Operation limit temperature		-20	°C				

Electricity

Electric power input in power modes other than "on mode"

Seasonal electricity consumption

off mode	Poff	0.026	kW	Cooling	QCE	495	kWh/a
standby mode	Psb	0.026	kW	Heating/Average	QHE/A	3045	kWh/a
thermostat-off mode	Pto	0.065	kW	Heating/Warmer	QHE/B	x	kWh/a
crankcase heater mode	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

Refrigerant

Type		R32					
Weight						2.60	kg
Global Warming Potential	GWP					675	kgCO ₂ eq.

Sound power level - db(A)

Rated air flow - m³/h

	Cooling	Heating		Cooling	Heating
RAV-GP1101AT8-E	66	67	RAV-GP1101AT8-E	6060	6060
RAV-RM561UTP-E	47	47	RAV-RM561UTP-E	1050	1050
RAV-RM561UTP-E	47	47	RAV-RM561UTP-E	1050	1050

Dimensions

	Height	Width	Depth	Weight
RAV-GP1101AT8-E	1340 mm	900 mm	320 mm	95 kg
RAV-RM561UTP-E	256 mm	840 mm	840 mm	20 kg
RAV-RM561UTP-E	256 mm	840 mm	840 mm	20 kg

Harmonised standard	EN14511:2007, EN12102
---------------------	-----------------------

Calculation methods - Measurement standards	PrEN 14825: 2011 chapter 8 and 9
---	----------------------------------

Contact details for obtaining more information	Importer/Distributor in EU: Toshiba Carrier UK Ltd. Porsham Close, Belliver Industrial Estate, PLYMOUTH, Devon, PL6 7DB. United Kingdom
--	---

Supplier	TOSHIBA CARRIER CORPORATION
----------	-----------------------------

Indoor unit	RAV-RM561UTP-E
-------------	----------------

Indoor unit	RAV-RM561UTP-E
-------------	----------------

Outdoor unit	RAV-GP1101AT8-E
--------------	-----------------

Sound power level

indoor unit (cooling)	dB	47
-----------------------	----	----

outdoor unit (cooling)	dB	66
------------------------	----	----

indoor unit (heating)	dB	47
-----------------------	----	----

outdoor unit (heating)	dB	67
------------------------	----	----

Refrigerant

Type		R32
------	--	-----

Global Warming Potential	kgCO ₂ eq	675
--------------------------	----------------------	-----

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 1975. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 1975 times higher than 1 kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

Cooling

Energy efficiency class		A++
-------------------------	--	-----

Design load (P _{designc})	kW	10.0
-------------------------------------	----	------

Seasonal efficiency (SEER)		7.06
----------------------------	--	------

Seasonal electricity consumption (Q _{CE})	kWh/annum	495
---	-----------	-----

Heating

		Heating/Average	Heating/Warmer	Heating/Colder
Energy efficiency class		A+	x	x
Design load (Pdesignh)	kW	9.5	x,x	x,x
Seasonal efficiency (SCOP)		4.36	x,xx	x,xx
Seasonal electricity consumption (Q _{HE})	kWh/annum	3045	x	x
Back up heating capacity	kW	2.11		
Declared capacity for heating, at indoor temperature 20°C and outdoor temperature Tj.				
Tj= -7°C (Pdh)	kW	8.40	-	x,xx
Tj= 2°C (Pdh)	kW	5.12	x,xx	x,xx
Tj= 7°C (Pdh)	kW	3.50	x,xx	x,xx
Tj= 12°C (Pdh)	kW	3.48	x,xx	x,xx
Tj=bivalent temperature (Pdh)	kW	8.40	x,xx	x,xx
Tj=operation limit (Pdh)	kW	4.03	x,xx	x,xx
Tj= -15°C (Pdh)	kW	-	-	x,xx