

Appliance - Split type air conditioner

Outdoor unit	Single Inverter	RAV-GP1101AT8-E
Indoor unit	Compact 4-way Cassette	RAV-RM561MUT-E
Indoor unit	Compact 4-way Cassette	RAV-RM561MUT-E

Function

Design load

Seasonal efficiency

Cooling	Y	Cooling	Pdesignc	10.0	kW	Cooling	SEER	6.16	A++
Heating - Average	Y	Heating/Average	Pdesignh	10.3	kW	Heating/Average	SCOP(A)	3.93	A
Heating - Warmer	N	Capacity control = Variable							
Heating - Colder	N								

Cooling

Capacity
Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.

Efficiency
Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.

Tj=35°C	Pdc	10.00	kW	Tj=35°C	EERd	3.85
Tj=30°C	Pdc	7.37	kW	Tj=30°C	EERd	5.76
Tj=25°C	Pdc	4.74	kW	Tj=25°C	EERd	7.77
Tj=20°C	Pdc	3.25	kW	Tj=20°C	EERd	10.83

Heating (Average climate)

Capacity
Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.

Efficiency
Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.

Tj=-7°C	Pdh	9.11	kW	Tj=-7°C	COPd	2.34
Tj=2°C	Pdh	5.55	kW	Tj=2°C	COPd	4.24
Tj=7°C	Pdh	3.57	kW	Tj=7°C	COPd	4.76
Tj=12°C	Pdh	2.92	kW	Tj=12°C	COPd	5.51
Tj=bivalent temperature	Pdh	9.11	kW	Tj=bivalent temperature	COPd	2.34
Tj=operation limit	Pdh	4.37	kW	Tj=operation limit	COPd	1.40
Bivalent temperature		-7	°C			
Operation limit temperature		-20	°C			

Electricity

Electric power input in power modes other than "on mode"

Seasonal electricity consumption

off mode	Poff	0.026	kW	Cooling	QCE	568	kWh/a
standby mode	Psb	0.026	kW	Heating/Average	QHE/A	3667	kWh/a
thermostat-off mode	Pto	0.086	kW	Heating/Warmer	QHE/B	x	kWh/a
crankcase heater mode	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

Refrigerant

Type		R32					
Weight						2.60	kg
Global Warming Potential	GWP					675	kgCO ₂ eq.

Sound power level - db(A)

Rated air flow - m³/h

	Cooling	Heating		Cooling	Heating
RAV-GP1101AT8-E	66	67	RAV-GP1101AT8-E	6060	6060
RAV-RM561MUT-E	59	59	RAV-RM561MUT-E	798	798
RAV-RM561MUT-E	59	59	RAV-RM561MUT-E	798	798

Dimensions

	Height	Width	Depth	Weight
RAV-GP1101AT8-E	1340 mm	900 mm	320 mm	95 kg
RAV-RM561MUT-E	256 mm	575 mm	575 mm	15 kg
RAV-RM561MUT-E	256 mm	575 mm	575 mm	15 kg

Harmonised standard EN14511:2007, EN12102

Calculation methods - Measurement standards PrEN 14825: 2011 chapter 8 and 9

Contact details for obtaining more information
Importer/Distributor in EU:
Toshiba Carrier UK Ltd.
Porsham Close, Belliver Industrial Estate,
PLYMOUTH, Devon, PL6 7DB.
United Kingdom

Supplier	TOSHIBA CARRIER CORPORATION
----------	-----------------------------

Indoor unit	RAV-RM561MUT-E
-------------	----------------

Indoor unit	RAV-RM561MUT-E
-------------	----------------

Outdoor unit	RAV-GP1101AT8-E
--------------	-----------------

Sound power level

indoor unit (cooling)	dB	59
-----------------------	----	----

outdoor unit (cooling)	dB	66
------------------------	----	----

indoor unit (heating)	dB	59
-----------------------	----	----

outdoor unit (heating)	dB	67
------------------------	----	----

Refrigerant

Type		R32
------	--	-----

Global Warming Potential	kgCO ₂ eq	675
--------------------------	----------------------	-----

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 1975. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 1975 times higher than 1 kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

Cooling

Energy efficiency class		A++
-------------------------	--	-----

Design load (P _{designc})	kW	10.0
-------------------------------------	----	------

Seasonal efficiency (SEER)		6.16
----------------------------	--	------

Seasonal electricity consumption (Q _{CE})	kWh/annum	568
---	-----------	-----

Heating

		Heating/Average	Heating/Warmer	Heating/Colder
Energy efficiency class		A	x	x
Design load (Pdesignh)	kW	10.3	x,x	x,x
Seasonal efficiency (SCOP)		3.93	x,xx	x,xx
Seasonal electricity consumption (Q _{HE})	kWh/annum	3667	x	x
Back up heating capacity	kW	2.28		
Declared capacity for heating, at indoor temperature 20°C and outdoor temperature Tj.				
Tj= -7°C (Pdh)	kW	9.11	-	x,xx
Tj= 2°C (Pdh)	kW	5.55	x,xx	x,xx
Tj= 7°C (Pdh)	kW	3.57	x,xx	x,xx
Tj= 12°C (Pdh)	kW	2.92	x,xx	x,xx
Tj=bivalent temperature (Pdh)	kW	9.11	x,xx	x,xx
Tj=operation limit (Pdh)	kW	4.37	x,xx	x,xx
Tj= -15°C (Pdh)	kW	-	-	x,xx