

## Appliance - Split type air conditioner

Outdoor unit	Single Inverter	RAV-GP1101AT-E
Indoor unit	4-WAY SMART CASSETTE	RAV-GM1101UT-E

Function		Design load			Seasonal efficiency				
Cooling	Y	Cooling	Pdesignc	10.0	kW	Cooling	SEER	8.80	A++
Heating - Average	Y	Heating/Average	Pdesignh	9.2	kW	Heating/Average	SCOP(A)	5.00	A++
Heating - Warmer	N	Capacity control = Variable							
Heating - Colder	N								

### Cooling

Capacity			Efficiency		
Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.			Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.		
Tj=35°C	Pdc	10.00 kW	Tj=35°C	EERd	5.26
Tj=30°C	Pdc	7.39 kW	Tj=30°C	EERd	7.32
Tj=25°C	Pdc	4.78 kW	Tj=25°C	EERd	11.12
Tj=20°C	Pdc	4.03 kW	Tj=20°C	EERd	16.12

### Heating (Average climate)

Capacity			Efficiency		
Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.			Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.		
Tj=-7°C	Pdh	8.14 kW	Tj=-7°C	COPd	3.42
Tj=2°C	Pdh	4.92 kW	Tj=2°C	COPd	4.97
Tj=7°C	Pdh	3.10 kW	Tj=7°C	COPd	6.46
Tj=12°C	Pdh	3.10 kW	Tj=12°C	COPd	7.95
Tj=bivalent temperature	Pdh	8.14 kW	Tj=bivalent temperature	COPd	3.42
Tj=operation limit	Pdh	1.63 kW	Tj=operation limit	COPd	1.01
Bivalent temperature		-7 °C			
Operation limit temperature		-27 °C			

## Electricity

Electric power input in power modes other than "on mode"

Seasonal electricity consumption

off mode	Poff	0.007	kW	Cooling	QCE	398	kWh/a
standby mode	Psb	0.007	kW	Heating/Average	QHE/A	2573	kWh/a
thermostat-off mode	Pto	0.111	kW	Heating/Warmer	QHE/B	x	kWh/a
crankcase heater mode	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

## Refrigerant

Type		R32					
Weight						3.10	kg
Global Warming Potential	GWP					675	kgCO <sub>2</sub> eq.

## Sound power level - db(A)

## Rated air flow - m<sup>3</sup>/h

	Cooling	Heating		Cooling	Heating
RAV-GP1101AT-E	66	67	RAV-GP1101AT-E	6960	6960
RAV-GM1101UT-E	61	61	RAV-GM1101UT-E	2250	2250

## Dimensions

	Height	Width	Depth	Weight
RAV-GP1101AT-E	1550 mm	1010 mm	370 mm	104 kg
RAV-GM1101UT-E	319 mm	840 mm	840 mm	25 kg

Harmonised standard	EN14511:2007, EN12102
---------------------	-----------------------

Calculation methods - Measurement standards	PrEN 14825: 2011 chapter 8 and 9
---	----------------------------------

Contact details for obtaining more information	Importer/Distributor in EU: Toshiba Carrier UK Ltd. Porsham Close, Belliver Industrial Estate, PLYMOUTH, Devon, PL6 7DB. United Kingdom
--	---

Supplier	TOSHIBA CARRIER CORPORATION
----------	-----------------------------

Indoor unit	RAV-GM1101UT-E
-------------	----------------

Outdoor unit	RAV-GP1101AT-E
--------------	----------------

## Sound power level

indoor unit (cooling)	dB	61
-----------------------	----	----

outdoor unit (cooling)	dB	66
------------------------	----	----

indoor unit (heating)	dB	61
-----------------------	----	----

outdoor unit (heating)	dB	67
------------------------	----	----

## Refrigerant

Type		R32
------	--	-----

Global Warming Potential	kgCO <sub>2</sub> eq	675
--------------------------	----------------------	-----

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 1975. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 1975 times higher than 1 kg of CO<sub>2</sub>, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

## Cooling

Energy efficiency class		A++
-------------------------	--	-----

Design load (P <sub>designc</sub> )	kW	10.0
-------------------------------------	----	------

Seasonal efficiency (SEER)		8.80
----------------------------	--	------

Seasonal electricity consumption (Q <sub>CE</sub> )	kWh/annum	398
---	-----------	-----

## Heating

		Heating/Average	Heating/Warmer	Heating/Colder
Energy efficiency class		A++	x	x
Design load (Pdesignh)	kW	9.2	x,x	x,x
Seasonal efficiency (SCOP)		5.00	x,xx	x,xx
Seasonal electricity consumption (Q <sub>HE</sub> )	kWh/annum	2573	x	x
Back up heating capacity	kW	2.04		
<b>Declared capacity for heating, at indoor temperature 20°C and outdoor temperature Tj.</b>				
Tj= -7°C (Pdh)	kW	8.14	-	x,xx
Tj= 2°C (Pdh)	kW	4.92	x,xx	x,xx
Tj= 7°C (Pdh)	kW	3.10	x,xx	x,xx
Tj= 12°C (Pdh)	kW	3.10	x,xx	x,xx
Tj=bivalent temperature (Pdh)	kW	8.14	x,xx	x,xx
Tj=operation limit (Pdh)	kW	1.63	x,xx	x,xx
Tj= -15°C (Pdh)	kW	-	-	x,xx