

Leverandør	TOSHIBA		
Model(s)	Utedel	HWT-401HW-E	
	Innedel	HWT-601XWHM6W-E	
	Hot water cylinder		
For space heating	Application	Medium Temperature application (indoor outlet water temperature 55°C)	
For water heating	Declared load profile	-	
For space heating	Seasonal space heating energy efficiency class	Average climate	A++
For water heating	Water heating energy efficiency class	Average climate	-
For space heating	Rated heat output	Average climate	5 kW
For space heating	Annual energy consumption	Average climate	2721 kWh
For space heating	Seasonal space heating energy efficiency	Average climate	135 %
For water heating	Annual electricity consumption	Average climate	- kWh
For water heating	Water heating energy efficiency	Average climate	- %
Sound power level (Indoor unit)			40 dB
Off peak			-
Specific precaution			-
For space heating	Rated heat output	Colder climate	3 kW
		Warmer climate	5 kW
For space heating	Annual energy consumption	Colder climate	2833 kWh
		Warmer climate	1448 kWh
For water heating	Annual electricity consumption	Colder climate	- kWh
		Warmer climate	- kWh
For space heating	Seasonal space heating energy efficiency	Colder climate	108 %
		Warmer climate	169 %
For water heating	Water heating energy efficiency	Colder climate	- %
		Warmer climate	- %
Sound power level (Outdoor unit)			59.00 dB
Precautions on installation & maintenance are available in Installation Manuals and Service Manuals			

Carrier RLC Europe SAS

Authorised by Carrier Corporation as Toshiba HVAC products web site for Europe, Middle-East and Africa

A Carrier company

© 2024 Carrier. All rights reserved.

